

# ESB200NH40S

## Ultra-Fast Soft Recovery Diode Module


### Equivalent Circuit and Package

#### ■ Features

- Repetitive Reverse Voltage :  $V_{RRM} = 400V$
- Low Forward Voltage Drop :  $V_F(\text{typ.}) = 1.05V$
- Average Forward Current :  $I_F(\text{AV.}) = 200A @ T_c = 100^\circ\text{C}$
- Ultra-Fast Reverse Recovery Time :  $t_{rr}(\text{typ.}) = 150 \text{ ns}$
- Extensive Characterization of Recovery Parameters
- Reduced EMI and RFI
- Non Isolation Type Package

#### ■ Applications

- Welding Machine
- Induction Heating
- UPS



Please see the package outline information

#### ■ Absolute Maximum Ratings @ $T_c=25^\circ\text{C}$ (Per Leg)

Symbol	Parameter	Conditions	Ratings	Unit
$V_{RRM}$	Repetitive Peak Reverse Voltage		400	V
$V_{R(\text{DC})}$	Reverse DC Voltage		320	V
$I_{F(\text{AV})}$	Average Forward Current	$T_c = 25^\circ\text{C}$ $T_c = 100^\circ\text{C}$	400	A
			200	A
$I_{FSM}^{(1)}$	Surge(non-repetitive) Forward Current	One Half Cycle at 60Hz, Peak Value	2800	A
$I^2t$	$I^2t$ for Fusing	Value for One Cycle Current, $t_w = 8.3\text{ms}$ , $T_j = 25^\circ\text{C}$ Start	$3.25 \times 10^4$	$\text{A}^2\text{s}$
$T_j^{(2)}$	Junction Temperature	-	-40 ~ 125	$^\circ\text{C}$
$T_{stg}$	Storage Temperature	-	-40 ~ 125	$^\circ\text{C}$
$P_d$	Maximum Power Dissipation		1363	W
-	Mounting screw torque	M6	4.0	N.m
-	Mounting terminals screw torque	M6	3.0	N.m

(Note \*1) Repetitive rating : Pulse width limited by max junction temperature

(Note \*2) The maximum junction temperature of chip is  $175^\circ\text{C}$

## ■ Electrical Characteristics of FRD @ T<sub>c</sub>=25°C (unless otherwise specified)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
V <sub>R</sub>	Cathode Anode Breakdown Voltage	I <sub>R</sub> = 100uA	400	-	-	V
V <sub>FM</sub>	Maximum Forward Voltage	I <sub>FM</sub> = 200A	T <sub>j</sub> =25°C	-	1.05	1.4
			T <sub>j</sub> =125°C	-	0.95	-
I <sub>RRM</sub>	Repetitive Peak Reverse Current	T <sub>C</sub> = 100°C, V <sub>RRM</sub> applied	-	-	1.0	mA
t <sub>rr</sub>	Reverse Recovery Time	I <sub>FM</sub> = 200A, V <sub>R</sub> = 200V di/dt=-600A/us	T <sub>j</sub> =25°C	-	150	200
			T <sub>j</sub> =125°C	-	220	-

## ■ Thermal Characteristics and Weight

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
R <sub>θJC</sub>	Junction-to-Case	per FRD	-	-	0.11	°C/W
Weight	Weight of Module		-	-	95	g

## ■ Performance Curves

Fig. 1 Typical Forward Voltage Drop  
vs. Instantaneous Current




Fig. 2 Typical Reverse Recovery Time  
vs.  $-di/dt$




Fig. 3 Transient Thermal Impedance ( $Z_{thjc}$ ) Characteristics






Fig. 4 Forward Current Derating Curve



**■ Package Out Line Information****FD3 Package**Dimensions in mm**■ Internal Circuit**